

HORUS422A

2U 19" RUGGED RACKMOUNT
WITH INTEL® CORE I7-6700TE
12 BAYS 2.5" SSD/HDD, RAID SUPPORTED,
OPERATING TEMPERATURE 5~+50°C



- INTEL® 6TH GEN. CORE I7-6700TE
- 4 x DDR4 XR-DIMM UP TO 64GB
- ROCKETRAID 840A RAID CARD
- 4 x RJ45 LAN, 6 x USB, 1 x RS232 CONSOLE
- 12 x 2.5" EASY SWAP SSD/HDD TRAY
- EXTENDED TEMPERATURE 5~+50°C

SPECIFICATIONS

SYSTEM	
CPU Type	Intel® Core i7-6700TE Processor
Memory Type	4 x DDR4 XR-DIMM up to 64GB
Expansion slot	4 x mPCIe slot (two supported with mSATA) 1 x PCIe x4 slot
RAID Function	RocketRAID 840A RAID Card, support RAID 0,1,5,6,10,50,JBOD
Storage Device	12 x 2.5" (7mm) Easy swap HDD/SSD Tray
FRONT I/O INTERFACE	
USB	2 x USB 2.0
Console	1 x DB9 Console port
2.5" SSD/HDD Tray	12 (7mm height SSD/HDD only)
Power button	1 x System On/Off, 1 x System FAN On/Off
Indicator LED	1 x Power LED / 1 x HDD LED
REAR I/O INTERFACE	
USB	4 x USB 3.0
1 Gigabit Ethernet	4 x RJ45
Display	1 x DisplayPort 1 x HDMI
AC inlet	IEC C14 AC inlet
MECHANICAL AND ENVIRONMENT	
Power Requirement	AC to DC 100-240V 400W FLEX ATX Switch Power Supply with internal fan
Weight	TBC
Dimension	430x396x88mm (WxDxH)
Operating Temperature	5 to 50°C
Storage Temperature	-20 to 70°C
Relative Humidity	5% to 95%, non-condensing

ORDERING INFORMATION

HORUS422A

RUGGED RACKMOUNT

**2U 19" RUGGED RACKMOUNT WITH INTEL. CORE I7-6700TE,
12 BAYS 2.5" SSD/HDD, RAID SUPPORTED, OPERATING
TEMPERATURE 5~+50°C**

DIMENSIONS

